

23 6690

Medium weight cut level F arc flash glove

Code	23-6690		
Description	Medium weight cut level F arc flash glo		
Gauge	13gg		
Colour	Yellow liner / Black coating		
Cuff Style	Knit wrist		
Length	220-270		
Sizes	7-11		
Packaging	12 pairs/paper band, 72 pairs/carton		



eatures & Benefits

- Meets NFPA 70E requirements for arc flash PPE (Category 2)
- Achieves ATPV 11.7cal/cm² according to ASTM F2675/2675M
- Level F cut resistance to EN388:2016+A1:2018
- EN407:2020 Limited flame spread level 4
- EN407:2020 Contact heat level 1
- Neoprene foam palm coating provides excellent wet and dry grip
- Robust 13gg aramid liner for heavy duty handling applications











Performance







Sizing Cuff Colours

Size	7 Small	8 Medium	9 Large	10 X-Large	11 2X-Large
Colour coded cuff					

applications / Industries

- Environments with heat, flame and potential for arc-flash risks
- Oil and gas processing and refineries
- Heavy equipment and vehicle maintenance
- Electrical equipment operation and maintenance
- Construction
- Metal handling and stamping









Tilsatec | +44 (0)1924 375742 | info@tilsatec.com | www.tilsatec.com