

# 55-5110

Lightweight, cut level E PU gloves with best in class cut protection, dexterity, tactility\* and grip



Tilsatec | +44 (0)1924 375742 | [info@tilsatec.com](mailto:info@tilsatec.com) | [www.tilsatec.com](http://www.tilsatec.com)

For businesses who want expertise they can rely on to keep their people safe, Tilsatec offer high performance hand and arm protection. We manufacture our own proprietary cut resistant yarn - the primary source of mechanical protection, on site in the UK. This means we can deliver maximum performance in every fibre of what we do. Because when our gloves perform at their best, your people can perform at their best.

# 55-5110

Lightweight cut resistant PU palm coated glove



The 55-5110 is part of the range of 15 gauge lightweight high cut gloves. The form-fitting soft, comfortable liner moulds to the contours of the hand, whilst delivering level E cut protection to EN388: 2016. The dry, lightweight polyurethane palm coating is robust and durable, providing uncompromising dry grip and oil grip with incredible dexterity and tactility for this level of cut protection.

## Features & Benefits

- EN388: 2016 level E cut resistance
- Rhino Yarn™ cut resistant technology
- Fine 15 gauge lightweight liner with high dexterity
- Durable PU palm coating provides good grip
- Dark colour liner hides dirt, extending life of the glove
- Smooth and comfortable, form-fitting seamless liner

## Applications / Industries

- Assembly
- Automotive industry
- Light metal fabrication / stamping
- Construction
- White goods manufacturing

\*best in class 15 gauge glove delivering EN388: 2016 level E cut protection

Code	Description	Gauge	Colour	Cuff Style	Length	Sizes	Packaging
55-5110	Lightweight cut resistant PU palm coated glove	15gg	Black liner Grey coating	Knit wrist	220-270mm	7/S - 11/2XL	12 pairs/polybag 120 pairs/carton

<http://tilsatec.com/products/55-5110-cut-e-pu-palm-coated-glove>

## Performance

EN388: 2016



3 X 4 3 E

Antistatic according to the requirements of EN 1149-5 : 2008 using EN 1149-3 : 2004 induction charging test method.



**RHINOYARN®**

Made with Tilsatec Rhino Yarn technology. Produced in the UK and developed by Tilsatec's specialist team of yarn technologists to deliver the optimum in performance and comfort.

Tilsatec | +44 (0)1924 375742 | [info@tilsatec.com](mailto:info@tilsatec.com) | [www.tilsatec.com](http://www.tilsatec.com)

For businesses who want expertise they can rely on to keep their people safe, Tilsatec offer high performance hand and arm protection. We manufacture our own proprietary cut resistant yarn - the primary source of mechanical protection, on site in the UK. This means we can deliver maximum performance in every fibre of what we do. Because when our gloves perform at their best, your people can perform at their best.