

53 7121

NEW for 2021

Lightweight cut level **F** sandy foam nitrile palm coated glove with reinforcement

Code	53-7121
Description	Lightweight cut level F sandy foam nitrile coated glove with reinforcement
Gauge	13gg
Colour	Grey liner / Black coating
Cuff Style	Knit wrist
Length	220-270mm
Sizes	6/XS - 11/2XL
Packaging	12 pairs/polybag 120 pairs/carton



Features & Benefits

- EN388: 2016 level F cut resistance
- New Rhino Yarn™ composition using lighter, finer steel
- Additional black nitrile reinforcement to thumb crotch for high action area increasing lifespan of glove
- EN407:2020 contact heat level 1
- 360 breathability reduces perspiration
- Sandy foam nitrile palm coating provides good wet and dry grip
- New back of hand markings



Applications / Industries

- Assembly
- Automotive industry
- Light metal fabrication / stamping
- Glass Manufacturing
- White goods manufacturing



Performance

EN388: 2016




4 X 4 2 F

EN407:2020



X 1 X X X X







ANSI 105: 2016



CUT



Sizing Cuff Colours

Size	6 X-Small	7 Small	8 Medium	9 Large	10 X-Large	11 2X-Large
Colour coded cuff						

tilsatec.com/products/lightweight-cut-level-f-foam-nitrile-coated-glove-thumb-reinforcement-53-7121



Made with Tilsatec Rhino Yarn™ technology. Produced in the UK and developed by Tilsatec's specialist team of yarn technologists to deliver the optimum in performance and comfort.