

49-6220

Rhinoquard™ mechanics glove



Features & Benefits

- EN388: 2016 level E cut resistance
- Rhino Yarn™ cut resistant technology
- EN388: 2016 level 4 puncture resistance
- ASTM F2878-10 hypodermic needle test: 5.7 Newtons
- Leather reinforcement for high action areas
- Rubber pull tab for quick donning and doffing
- Neoprene expandable wrist for safety and comfort

RHINOGUARD

Extreme Cut & Puncture Protection

RHINOGUARD™ is a highly engineered textile composite designed to provide the highest levels of protection against a wide range of puncture hazards. Constructed from an innovative combination of advanced fibres, modified fabric structure and a unique coating technology to deliver high levels of protection against both large and small puncture threats (including needles and syringes).

The RHINOGUARD™ mechanics glove delivers cut, abrasion, puncture and needle resistance in a powerful combination of mechanical protection for extreme working conditions. The areas of the glove with RHINOGUARD™ inside include the palm, fingers, finger crotches and fingertips to ensure the most exposed regions to hazards have full protection coverage.

Applications / Industries

- Emergency services:
- Police, Fire Fighters, Search and Rescue.
- Security services
- Local authorities, house clearance teams
- Waste management
- Metal forming / handling

Code	Description	Gauge	Colour	Cuff Style	Length	Sizes	Packaging
49-6220	Mechanics glove with Rhinoguard™	N/A	Grey	Neoprene	230 - 270mm	7/S - 11/2XL	Packed per pair 36 pairs/carton

http://tilsatec.com/products/49-6220-rhinoguard-mechanics-glove





Made with Tilsatec Rhino Yarn technology. Produced in the UK and developed by Tilsatec's specialist team of yarn technologists to deliver the optimum in performance and comfort.

Tilsatec | +44 (0)1924 375742 | info@tilsatec.com | www.tilsatec.com