

Tilsatec | +44 [0]1924 375742 | info@tilsatec.com | www.tilsatec.com

For businesses who want expertise they can rely on to keep their people safe, Tilsatec offer high performance hand and arm protection. We manufacture our own proprietary cut resistant yarn - the primary source of mechanical protection, on site in the UK. This means we can deliver maximum performance in every fibre of what we do. Because when our gloves perform at their best, your people can perform at their best.



55-5120 / 55-5123 NEW

Level E cut protection combined with oil grip, dexterity and tactility





Features & Benefits

- EN388: 2016 level E cut resistance
- Rhino Yarn™ cut resistant technology
- 15 gauge form-fitting, lightweight liner
- · High level of tactility and dexterity
- Micropore nitrile coating delivers good dry and oil grip
- Flat nitrile full dip provides oil repellency and liquid protection keeping hands dry and comfortable



Applications / Industries

- Assembly
- Automotive industry
- Metal fabrication / stamping / press
- Glass manufacturing
- Construction
- White goods manufacturing

*best in class 15 gauge glove delivering EN388: 2016 level E cut protection

Code	Description	Gauge	Colour	Cuff Style	Length	Sizes	Packaging
55-5120	Lightweight cut resistant micropore nitrile palm coated glove	15gg	Black liner Black coating	Knit wrist	230-270mm	7/S - 11/2XL	12 pairs/polybag 120 pairs/carton
55-5123	Lightweight cut resistant fully coated nitrile with micropore nitrile palm coated glove	15gg	Black liner Black coating	Knit wrist	230-270mm	7/S - 11/2XL	12 pairs/polybag 120 pairs/carton

http://tilsatec.com/products/55-5120-cut-e-nitrile-palm-coated-glove https://tilsatec.com/products/55-5123-cut-e-fully-coated-nitrile-glove

Performance





3 X 4 3 E

Antistatic according to the requirements of EN 1149-5 : 2008 using EN 1149-3 : 2004 induction charging test method.



Made with Tilsatec Rhino Yarn technology. Produced in the UK and developed by Tilsatec's specialist team of yarn technologists to deliver the optimum in performance and comfort.

Tilsatec | +44 (0)1924 375742 | info@tilsatec.com | www.tilsatec.com